

# 332RS9



Products → Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe  
→ Surface Socket Outlets

## General Information

<b>Extended Product Type:</b>	332RS9
<b>Product ID:</b>	2CMA193132R1000
<b>EAN:</b>	7392696931328
<b>Catalog Description:</b>	Surface socket-outlet, 9h, 32A, IP44, 3P+E
<b>Long Description:</b>	Surface socket-outlet, earthing sleeve position 9h, rated current 32A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Blue

## Ordering

<b>EAN:</b>	7392696931328
<b>Minimum Order Quantity:</b>	10 piece
<b>Country of Origin:</b>	Czech Republic (CZ)

## Dimensions

<b>Product Net Width:</b>	85 mm
<b>Product Net Height:</b>	118 mm
<b>Product Net Length:</b>	163 mm
<b>Product Net Depth:</b>	163 mm
<b>Product Net Weight:</b>	0.32 kg

## Container Information

<b>Package Level 1 Width:</b>	188 mm
<b>Package Level 1 Length:</b>	175 mm
<b>Package Level 1 Height:</b>	428 mm
<b>Package Level 1 Gross Weight:</b>	3.2 kg
<b>Package Level 1 EAN:</b>	7392696661324
<b>Package Level 1 Units:</b>	10 piece
<b>Package Level 2 Units:</b>	240 piece

## Certificates and Declarations (Document Number)

<b>Declaration of Conformity - CE:</b>	2CMC700005D0001
<b>Declaration:</b>	2CMC700005D0001
<b>Environmental Information:</b>	2CMC700001D0002
<b>RoHS Information:</b>	2CMC700057D0001
<b>SEMKO Certificate:</b>	1613211

## Additional Information

<b>Additional Information:</b>	3P+E
<b>Cable Cross-Section:</b>	2.5 ... 10 mm <sup>2</sup>
<b>Cable Diameter:</b>	22 mm
<b>Cable Entry Position:</b>	Cable entry, flexible membrane and metric threaded M25 insert for top cable entry.Rear knock-out cable entry.
<b>Color:</b>	Blue
<b>Connection Type:</b>	Screw clamp
<b>Degree of Protection:</b>	IP44
<b>Enclosure Material:</b>	Thermoplastic
<b>Frequency (f):</b>	50 Hz 60 Hz
<b>Function:</b>	Surface socket outlet
<b>Housing Material:</b>	Plastic (PA)
<b>Invoice Description:</b>	Ind. P&S#332RS9
<b>Mounting Holes:</b>	111x72
<b>Number of Poles:</b>	4
<b>Product Main Type:</b>	ERS
<b>Product Name:</b>	Wall mounted socket
<b>Protection Type:</b>	Splashproof
<b>Rated Current (I<sub>n</sub>):</b>	32 A
<b>Rated Voltage (U<sub>r</sub>):</b>	200 ... 250 V
<b>Recommended Screw Driver:</b>	PH2
<b>RoHS Date:</b>	L23
<b>Standards:</b>	IEC 60309-1 IEC 60309-2
<b>Suitable For:</b>	Surface Socket Outlets
<b>Suitable for Product Class:</b>	Industrial Plugs and Sockets

## Classifications

<b>eClass:</b>	27440510
<b>E-nummer:</b>	2416499
<b>UNSPSC:</b>	39120000

