

PRODUCT-DETAILS

OT125F3C

OT125F3C CHANGE-OVER SWITCH



Informações gerais

Extended Product Type	OT125F3C
Product ID	1SCA105037R1001
EAN	6417019391670
Catalog Description	OT125F3C CHANGE-OVER SWITCH
Long Description	Handle and shaft has to be ordered separately

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301067M0208

Dimensions

Product Net Width	140 mm
Product Net Height	100 mm

Product Net Depth / Length	86 mm
Product Net Weight	0.9 kg

Technical

Rated Operational Current AC-21A (I _e)	(380 ... 415 V) 125 A (500 V) 125 A (690 V) 125 A
Rated Operational Current AC-22A (I _e)	(380 ... 415 V) 125 A (500 V) 125 A (690 V) 125 A
Rated Operational Current AC-23A (I _e)	(380 ... 415 V) 90 A (500 V) 70 A (690 V) 50 A
Rated Operational Power AC-23A (P _e)	(380 ... 415 V) 45 kW (500 V) 45 kW (690 V) 45 kW
Conventional Free-air Thermal Current (I _{th})	q = 40 °C 125 A
Conventional Thermal Current (I _{the})	Fully Enclosed 125 A
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Rated Insulation Voltage (U _i)	750 V
Rated Operational Voltage	750 V
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 1 s 2.5 kiloampere rms
Power Loss	6.3 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft not included Mechanism on Top of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Standards	UL 98 / IEC60947-3
Mounting Type	Base mounting
Number of Poles	3
Cable Cross-Section	10 ... 70 mm²
Degree of Protection	Front IP20
Mechanical Durability	6000 cycle
Transition Type	Open

Technical UL/CSA

Horsepower Rating UL/CSA	(acc. to UL 200 V) 30 Hp (acc. to UL 208 V) 30 Hp (acc. to UL 240 V) 30 Hp (acc. to UL 480 V) 50 Hp (acc. to UL 600 V) 50 Hp
Ampere Rating UL/CSA	100 A

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC303021D0201
Instructions and Manuals	1SCC301067M0208
RoHS Information	1SCC301183D0201

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	102 mm
Package Level 1 Depth / Length	205 mm
Package Level 1 Height	103 mm
Package Level 1 Gross Weight	0.9 kg
Package Level 1 EAN	6417019391670

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
UNSPSC	39122233
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601411
E-Number (Sweden)	3171266

Categorias

Produtos e Sistemas de Baixa Tensão → Chaves seccionadoras → Chaves comutadoras e de transferência → Chaves comutadoras

