

PRODUCT-DETAILS

ACS880-01-24A3-2

ACS880-01-24A3-2 Pcont.max:5,5kW, Icont.max:23,1A



Informações gerais

Global Commercial Alias	ACS880-01-24A3-2
Product ID	3AUA0000123755
ABB Type Designation	ACS880-01-24A3-2
Catalog Description	ACS880-01-24A3-2 Pcont.max:5,5kW, Icont.max:23,1A

Ordering

Country of Origin	Finland (FI)
Customs Tariff Number	85044088
Invoice Description	ACS880-01-24A3-2 Pcont.max:5,5kW, Icont.max:23,1A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions

Product Net Height	409 mm
Product Net Length	249 mm

Product Net Width	155 mm
-------------------	--------

Technical

Enclosure Class	IP21
Frequency (f)	50/60 Hz
Input Voltage (U _{in})	208 ... 240 V
Mounting Type	Wall-mounting
Number of Phases	3
Output Current, Heavy-Duty Use	16.8 A
Output Current, Light-Overload Use	23.1 A
Output Current, Normal Use	24.3 A
Output Power, Heavy-Duty Use	4 kW
Output Power, Light-Overload Use	5.5 kW
Output Power, Normal Use	5.5 kW

Additional Information

Product Main Type	ACS880-01-24A3-2
Product Name	Frequency Converter

Classifications

Product Series	ACS880
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
ETIM 7	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Categorias

Drives, inversores e conversores → Drives AC - Baixa Tensão → Industrial Drives - ACS 800 → ACS880 single drives → ACS880-01 - Wall-mounted single drive

