

PRODUCT-DETAILS

ACS880-01-414A-5

ACS880-01-414A-5 Pcont.max:250kW, Icont.max:393A



Informações gerais

Global Commercial Alias	ACS880-01-414A-5
Product ID	3AUA0000090447
ABB Type Designation	ACS880-01-414A-5
Catalog Description	ACS880-01-414A-5 Pcont.max:250kW, Icont.max:393A

Ordering

Country of Origin	Finland (FI)
Customs Tariff Number	85044088
Invoice Description	ACS880-01-414A-5 Pcont.max:250kW, Icont.max:393A
Made To Order	Yes
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

Dimensions

Product Net Height	955 mm
Product Net Length	412 mm

Product Net Width	380 mm
-------------------	--------

Technical

Enclosure Class	IP21
Frequency (f)	50/60 Hz
Input Voltage (U _{in})	380 ... 500 V
Mounting Type	Wall-mounting
Number of Phases	3
Output Current, Heavy-Duty Use	361 A
Output Current, Light-Overload Use	393 A
Output Current, Normal Use	414 A
Output Power, Heavy-Duty Use	200 kW
Output Power, Light-Overload Use	250 kW
Output Power, Normal Use	250 kW

Additional Information

Product Main Type	ACS880-01-414A-5
Product Name	Frequency Converter

Classifications

Product Series	ACS880
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)
ETIM 7	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

Categorias

Drives, inversores e conversores → Drives AC - Baixa Tensão → Industrial Drives - ACS 800 → ACS880 single drives → ACS880-01 - Wall-mounted single drive

